



P.J.M. INDUSTRIAL (Australia)

Light Weight 25/30 Tonne **Mono Strand Jacks**



Safety Relief Valve set at 700 Bar

Vertically or Horizontally mount couplers easily.

All Jacks have the ability to accept 0.5 (1/2") & 0.6 (5/8") Strand.
c/w carry handle, Spring Loaded Nose, or Solid Nose
Fitted with Safety Relief Valve
&
Your choice of coupler set up
Horizontal or Vertical,
2 x Male or 2 x Female or Male & Female.

	25T	30T
Outside Dia:	100mm	108mm
Bore:	82.55mm	88.9mm
Inner OD	50.8mm	50.8mm
Area:	33.886 sq/cm	42.43 sq/cm
Piston Rod Dia:	66.6mm	66.6mm
Centre Hole:	24mm	24mm
Working Pressure:	23.72T @ 700 Bar	29.7T @ 700 Bar
PJM-25150-CHDA	Closed Length:	345mm 15kg
PJM-25200-CHDA	" "	400mm 18kg
PJM-30200-CHDA	" "	400mm 21kg
PJM-25300-CHDA	" "	495mm 21kg
PJM-25450-CHDA	" "	645mm 29kg
PJM-25600-CHDA	" "	805mm 35kg
PJM-30600-CHDA	" "	805mm 40kg

*** ANTI ROTATION & HYDRAULIC SEATING CAN ALSO BE FITTED**

Fact 15/34 Christensen Street,
Cheltenham Victoria
Australia 3192

**Hydraulic Jacking & Maintenance
Equipment**

Phone: 61 3 9553 4882
Fax: 61 3 9553 4883

Email: peter@pjmindustrial.com.au