

ww-HP-50t

Hydraulic Workshop Press 50 t

ISO9001 : 2008 | Made in Eichstätt / Germany

Operation pressure 700 bar
Time and space saving
Maintenance free
Fast press table adjustment
Protective screen

Applicable in automobile, commercial vehicle, agricultural machine workshops, as well as mechanical shops. Ideal for force fitting and extraction of bearings, bushings, shafts and bolts. Perfectly suited for embossing, bending, aligning and stamping. Press table can be positioned both up and down side by cable winch that allows the handling of various work pieces.

Technical Data

Type	ww-HP-50t
Capacity	50 ton / 492 kN
Hydraulic Pump	700 bar 220V / 380V
Cylinder type	Double acting
Height	2050 mm
Width	1250 mm
Lowest insert height	550 mm
Boring distance in height	140 mm
Inner width	780 mm
Width between columns	300 mm
Cylinder stroke	300 mm
Weight	630 kg

SCOPE OF SUPPLY

Rugged frame press with press table
Protective screen, Double acting cylinder
Elect.power unit, Manometer
1 pressure tappet flat, 2 base plates

ACCESSORIES FOR ww-HP-50t



ww-AP-50-1

- 2 x base plate with borehole diameter 100




ww-AP-50-2

- 2 x base plate with prism



With the use of
electro hydraulic power unit



ww-AP-50-4

- 2 x base plate with milled prism

ADDITIONAL ORDER VERSION

Single acting hydraulic cylinder with with pneumatic pump.



With the use of
air hydraulic pump