



**P.J.M. INDUSTRIAL (Australia)**

# Light Weight 25/30 Tonne Mono Strand Jacks



Safety Relief Valve set at 700 Bar

Vertically or Horizontally mount couplers Easily Changed

All Jacks have the ability to accept 0.5 (1/2") & 0.6 (5/8") Strand.  
c/w carry handle, Spring Loaded Nose, or Solid Nose  
**Fitted with Safety Relief Valve**  
&  
Your choice of coupler set up  
Horizontal or Vertical,  
2 x Male or 2 x Female or Male & Female.

	25T	30T
Outside Dia:	100mm	108mm
Bore:	82.55mm	88.9mm
Inner OD	50.8mm	50.8mm
Area:	33.886 sq/cm	42.43 sq/cm
Piston Rod Dia:	66.6mm	66.6mm
Centre Hole:	24mm	24mm
Working Pressure:	23.72T @ 700 Bar	29.7T @ 700 Bar

PJM-25150-CHDA	Closed Length:	345mm	15kg
PJM-25200-CHDA	" "	400mm	18kg
PJM-30200-CHDA	" "	400mm	21kg
PJM-25300-CHDA	" "	495mm	21kg
PJM-25450-CHDA	" "	645mm	29kg
PJM-25600-CHDA	" "	805mm	35kg
PJM-30600-CHDA	" "	805mm	40kg

**\* INTERNAL ANTI ROTATION & HYDRAULIC SEATING CAN ALSO BE FITTED**

Fact 29,26-28 Roberna Street,  
Moorabbin Victoria  
Australia 3189

**Hydraulic Jacking & Maintenance  
Equipment**

Phone: 61 3 9553 4882  
Fax: 61 3 9553 4883

Email: [peter@pjmindustrial.com.au](mailto:peter@pjmindustrial.com.au)