

## Low profile hydraulic torque wrench reducer



### Products Feature

- High strength alloy steel materials
- According to DIN standard 3121&3129
- The metric size reducers are as below, can be customized English or non-standard sockets

Wrench Model	Hex Link	Hex Size (mm)	Reducer Model						Locking Ring Model
			Model	A/B(mm)	Model	A/B(mm)	Model	A/B(mm)	
PHX02	HX02 -50	50	2G5041	50/41	2G5036	50/36	2G5032	50/32	H-50
	HX02 -46	46	2G4636	46/36	2G4632	46/32	2G4630	46/30	H-46
	HX02 -41	41	2G4132	41/32	2G4130	41/30	2G4127	41/27	H-41
	HX02 -36	36	2G3630	36/30	2G3627	36/27			H-36
	HX02 -32	32	2G3227	32/27					H-32
	HX02 -30	30							
	HX02 -27	27							
PHX05	HX05 -65	65	4G6555	65/55	4G6550	65/50	4G6546	65/46	H-65
	HX05 -60	60	4G6050	60/50	4G6046	60/46	4G6041	60/41	H-60
	HX05 -55	55	4G5546	55/46	4G5541	55/41	4G5536	55/36	H-55
	HX05 -50	50	4G5041	50/41	4G5036	50/36	4G5032	50/32	H-50
	HX05 -46	46	4G4636	46/36	4G4632	46/32	4G4630	46/30	H-46
	HX05 -41	41	4G4132	41/32	4G4130	41/30	4G4127	41/27	H-41
	HX05 -36	36	4G3630	36/30	4G3627	36/27			H-36
	HX05 -32	32	4G3227	32/27					H-32
	HX05 -30	30							
PHX10	HX10 -90	90	8G9080	90/80	8G9075	90/75	8G9070	90/70	H-90
	HX10 -85	85	8G8575	85/75	8G8570	85/70	8G8565	85/65	H-85
	HX10 -80	80	8G8070	80/70	8G8065	80/65	8G8060	80/60	H-80
	HX10 -75	75	8G7565	75/65	8G7560	75/60	8G7555	75/55	H-75
	HX10 -70	70	8G7060	70/60	8G7055	70/55	8G7050	70/50	H-70
	HX10 -65	65	8G6555	65/55	8G6550	65/50	8G6546	65/46	H-65
	HX10 -60	60	8G6050	60/50	8G6046	60/46			H-60

	HX10 -55	55	8G5546	55/46	8G5541	55/41			H-55
	HX10 -50	50							
PHX20	HX20 -115	115	14G115105	115/105	14G115100	115/100	14G11595	115/95	H-115
	HX20 -110	110	14G110100	110/100	14G11095	110/95	14G11090	110/90	H-110
	HX20 -105	105	14G10595	105/95	14G10590	105/90	14G10585	105/85	H-105
	HX20 -100	100	14G10090	100/90	14G10085	100/85	14G10080	100/80	H-100
	HX20 -95	95	14G9585	95/85	14G9580	95/80	14G9575	95/75	H-95
	HX20 -90	90	14G9080	90/80	14G9075	90/75	14G9070	90/70	H-90
	HX20 -85	85	14G8575	85/75	14G8570	85/70	14G8565	85/65	H-85
	HX20 -80	80	14G8070	80/70	14G8065	80/65			H-80
	HX20 -75	75	14G7565	75/65					H-75
	HX20 -70	70							
	HX20 -65	65							
PHX25	HX25 -135	135	18G135130	135/130	18G135120	135/120	18G135115	135/115	H-135
	HX25 -130	130	18G130120	130/120	18G130115	130/115	18G130110	130/110	H-130
	HX25 -120	120	18G120110	120/110	18G120105	120/105	18G120100	120/100	H-120
	HX25 -115	115	18G115105	115/105	18G115100	115/100	18G11595	115/95	H-115
	HX25 -110	110	18G110100	110/100	18G11095	110/95	18G11090	110/90	H-110
	HX25 -105	105	18G10595	105/95	18G10590	105/90	18G10585	105/85	H-105
	HX25 -100	100	18G10090	100/90	18G10085	100/85	18G10080	100/80	H-100
	HX25 -95	95	18G9585	95/85	18G9580	95/80	18G9575	95/75	H-95
	HX25 -90	90	18G9080	90/80	18G9075	90/75			H-90
	HX25 -85	85	18G8575	85/75					H-85
	HX25 -80	80							
	HX25 -75	75							
PHX40	HX40 -155	155	30G155145	155/145	30G155130	155/130	30G155120	155/120	H-155
	HX40 -145	145	30G145130	145/130	30G145120	145/120	30G145115	145/115	H-145
	HX40 -130	130	30G130120	130/120	30G130115	130/115	30G130110	130/110	H-130
	HX40 -120	120	30G120110	120/110	30G120105	120/105	30G120100	120/100	H-120
	HX40 -115	115	30G115105	115/105	30G115100	115/100	30G11595	115/95	H-115
	HX40 -110	110	30G110100	110/100	30G11095	110/95	30G11090	110/90	H-110
	HX40 -105	105	30G10595	105/95	30G10590	105/90	30G10590	105/90	H-105
	HX40 -100	100	30G10090	100/90	30G10085	100/85	30G10080	100/80	H-100
	HX40 -95	95	30G9585	95/85	30G9580	95/80			H-95
	HX40 -90	90	30G9080	90/80					H-90
	HX40 -85	85							
	HX40 -80	80							

Above as the standard working head and standard transition set, if you want to order non-standard products please specify the diameter of bolt, nut, bolts of grade and other specific requirements, such as unclear, please continue to send PJM consulting engineers.