










Lifting Slings Australia

Round Slings - Flat Webbing Slings - Ratchet Tie Down Lashings

Flat Webbing Slings

Lifting Slings Australia's flat webbing slings can be used for handling all modes of shipping, freight and load consignments. The slings are made of a coated and treated polyester yarn that does not damage refined, polished or fragile surfaces and will exert less pressure than wire ropes and chain at the point of contact with the load.

Colour coded according to DIN-EN 1492-1	Working Load Limits with 1 Webbing Slings					Working Load Limits with 2 Webbing Slings			
	Straight Lift	Chocked Lift	Parallel	90°	120°	Straight lift up to 45	Chocked lift up to 45	Straight lift 45-60	Straight lift 45-60
									
	1,0	0,8	2,0	1,4	1,0	1,4	1,12	1,0	0,8
WLL 1T	1000	800	2000	1400	1000	1400	1120	1000	800
WLL 2T	2000	1600	4000	2800	2000	2800	2240	2000	1600
WLL 3T	3000	2400	6000	4200	3000	4200	3360	3000	2400
WLL 4T	4000	3200	8000	5600	4000	5600	4480	4000	3200
WLL 6T	6000	4800	12000	8400	6000	8400	6720	6000	4800

All Slings manufactured to AS 1353.1-1997. These slings are colour coded with 7:1 safety factor.