

ww-HP-25t

Hydraulic Press 25 t

ISO9001 : 2008 | Made in Eichstätt / Germany

Operation pressure 700 bar
Time and space saving
Maintenance free
Fast press table adjustment
Foot or hand pump operation

Applicable in automobile, commercial vehicle, agricultural machine workshops, as well as mechanical shops. Ideal for force fitting and extraction of bearings, bushings, shafts and bolts. Perfectly suited for embossing, bending, aligning and stamping. Press table can be positioned both up and down side by cable winch that allows the handling of various work pieces.

Technical Data

Type	ww-HP-25t
Capacity	25ton / 246 kN
Hydraulic pump	Hand / Foot / Pneumatic
Cylinder type	Single acting
Height	1850 mm
Width	850 mm
Width between columns	540 mm
Lowest insert height	350 mm
Bore distance in height	100 mm
Table support width	180 mm
Cylinder stroke	150 mm
Weight	130 kg



With the use
of hand pump



ww-AP-25-1

ADDITIONAL ORDER VERSION

It can be supplied with foot,
hand or air hydraulic pump

Accessories for hydraulic press ww-HP-25t

- Force extraction plate
- 2 variable force extraction plate
- Diameter 40, dia. 20, dia. 16, dia. 30, dia. 65



With the use of
air hydraulic pump

SCOPE OF SUPPLY

Rugged frame press with press table.
Single acting cylinder. Hydraulic hand pump
Manometer and accessory set:
1 pressure tappet flat, 1 pressure tappet conical.
2 base plates, ready to use assembly.