

HYDRAULIC HAND PUMPS

Max. Working Pressure 1250 bar



PHP-1P4-3-2.2



PHP-2P4-2-13-A



PHP-2P4-2-5

Features

- Heavy duty construction with hardened ground and plated piston.
- Replaceable cartridge valves.
- Durable polyurethane plunger seal.
- Collapsible handle - faster stroke at low pressure.

PUMP SERIES	Pump Stage	Oil Tank Capacity (Ltrs.)	Model	Pressure (kg/cm ²)		Flow / stroke (cc)		Customized	Handle Effort (kg)
				1" stage	2" stage	1" stage	2" stage		
Single	1, 1.8, 2.2, 3		PHP-1P3-4-*	-	1250	-	2.0	—	40
			PHP-1P4-3-*	-	1000	-	2.8		
			PHP-1P4-2-#	-	700	-	2.8	Side mounted RH-B	
			PHP-1P5-1-#	-	350	-	5.0	Side mounted LH-C	
Two	5.8, 13.20		PHP-2P4-3-*	30	1000	49	2.8	Double acting with load holding - A Rotary DCV - E	
			PHP-2P4-2-#	30	700	49	2.8		
			PHP-2P5-1-#	30	350	49	5.0		

* Specify oil tank capacity in liters

Customized (Specify B, C, A)

- Higher capacity and customized solutions on request.
- Specifications are subject to change due to continual improvement.